



V-RAD Series are a new generation of electric torque wrenches used for the installation or removal of heavy duty fasteners where accuracy, power, and safety are required. This series comes without the hassle of air hoses and simply runs when plugged into any electric power supply, including generators. Based on the design of our patented planetary gear reduction system, the V-RAD Series offers a smooth continuous flow of controlled torque which is adjustable through dial settings.

Quick adjust torque settings

Fast and accurate "dial a torque" for maximum versatility and efficiency

Soft-start vary speed trigger

Allows operator to safely and quickly set reaction arm before full torque is applied

Equal power in forward & reverse

Convenience and cost effective use of same tool for break away and final torque

Advanced ultra-durable electric motor design

Extreme duty designed to reduce maintenance cost and increase reliability



V-RAD 6 Electric Powered Torque Tool

The V-RAD 6 Electric Series Tool offers a smooth continuous flow of controlled torque from 150 – 550 Nm which are adjustable through dial settings.

V-RAD 6 Electric Series Torque Tool

Part No.	Drive Size	Torque (Low- High)	RPM	Weight (kgs)	Noise Level
RAD-13589	0.75"	150 - 550 Nm	21	4.5	80 db



All V-RAD 6 Electric Torque Tools come fully calibrated complete with:

- V-RAD 6 Torque Tool
- Reaction Arm and Retention Ring
- Operators Manual
- Weatherproof Storage Case
- Calibration Chart

To ensure the highest quality of measurement and accuracy, each RAD® tool comes individually calibrated traceable to NIST standards.

Please contact us today

to arrange an on-site demonstration!

Toll Free 877-576-2855



Standard	Deep Socket	Double Ended	Blank	Double Ended Blank
RAD-10686	RAD-10687	RAD-10688	RAD-10036	RAD-10037

ALSO AVAILABLE FROM GLOBAL MINING PRODUCTS

BATTERY SERIES



Torque Range
150-1750 Nm

- ✓ Quick adjust torque settings
Fast and accurate “dial a torque” for maximum versatility and efficiency
- ✓ Soft-start vary speed trigger
Allows operator to safely and quickly set reaction arm before full torque is applied
- ✓ Equal power in forward and reverse
Convenience and cost effective use of same tool for break away and final torque
- ✓ Imagine the freedom – no air lines, no power cords!
The lightweight design of the B-SERIES makes them ideal for any application, especially where compressed air and electricity are not readily available.
- ✓ Advanced gearbox design
PATENTED planetary gear reduction drive system delivering one of the highest power-to-weight ratios of any controlled bolting system

ELECTRONIC SERIES



Torque Range
135-8100 Nm

- ✓ Push-button select torque
Fast and convenient error-free digital single increment torque setting
- ✓ Lightweight and ergonomic pistol grip design
Advance low-profile handle to reduce operator fatigue and increase productivity
- ✓ Extremely low noise level only 75db
World’s quietest extreme torque gun, ideal for sensitive environments and standards
- ✓ Data collection capability
All E Series tools come with data collection software allowing traceability of each torque sequence performed
- ✓ LED Green (Pass) or Red (Fail) indicator lights
Unmistakable visual signal indicates status of torque procedure for maximum accuracy and speed

PNEUMATIC SERIES



Torque Range
70-11500 Nm
Over 35 models available

- ✓ PATENTED planetary gear reduction
Delivers one of the highest power-to-weight ratios of any pneumatic controlled bolting system
- ✓ Smooth continuous flow of controlled torque
Eliminates destructive hammering
- ✓ Lightweight ergonomic pistol grip design
Reduces operator strain and injury; resulting in increased productivity
- ✓ Unmatched reliability and quality
Delivered by one of the most advanced engineered gear boxes on the market

CANADA

105 - 19289 Langley ByPass,
Surrey, B.C V3S 6K1
Phone. 604.576.2855
Fax. 604.576.2854

USA

400 Front Street,
Elko, NV 89801
Phone. 775.778.3410
Fax. 775.778.3418

INDONESIA

Jl. Kol. Syarifuddin Yoes RT.75 No. 04
Balikpapan 76115, East Kalimantan
Indonesia
Ph: (62) 05.4287.4097

